


Image not found or type unknown.



Technical information

Productnumber : 75.178.486.203



Product description

for more information see manual.

Advantages: For heavy transport on flat floors. Very low rolling resistance. Flat tread, hygienic.

Applications: Heavy material handling, heavy containers, automotive plants, petrochemical plants, heavy transport, ports, armed forces, aviation, bridge cranes, chemical companies.

Suitable surface: Hard and flat such as tiles, cement and coatings.

Suitable environment: Dry and not permanently damp. With different chemicals and with saturated steam.

Specifications

Article arrangement: New
Version: Ø 200 mm
Top: base plate 135x110 mm
Bolt hole: Ø 12.5 mm
Surface treatment: galvanized
Width (mm): 110
Loading capacity (kg): 800
Wheel bearing: ball bearing
EAN Code (Gtin) 8719424014136

Type: castor wheel with brake
Material: polyamide wheel
Hole centres: 105x80 mm
Colour: colorless
Length (mm): 140
Height (mm): 250
Weight (kg) 4
Type number: 757848

Scan the QR code for more information



KRUIZINGA.NL®
Opslag- en transportmiddelen

KRUIZINGA.DE®
Lager- und Transportmittel

KRUIZINGA.FR®
Stockage et ressources de transport

KRUIZINGA.COM®
Material handling equipment